

DECLARATION OF PERFORMANCE

NO: MONO 02

DRY- PRESSED CERAMIC TILE, WITH WATER ABSORPTION $6\% < E \leq 10\%$ FOR INTERNAL WALLS

NUOVA RIWAL CERAMICHE SRL , VIA GHIAROLA NUOVA 101, 41042
FIORANO MODENESE (MO) ITALIA

SYSTEM 4

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
Cadmium	NPD	
Lead	NPD	
Breaking Strength	>800 N for thick. > 7,5 mm > 500 N for thick. < 7,5 mm	
Slipperiness	NPD	
Tactility	NPD	
Bond strenght/adhesion, for:		
Cementitious adhesive, type C2	1N/mm ²	
Thermal Shock Resistance	PASS	
Durability for:		
_ Internal Use:	PASS	
_ External Use: freeze-thaw resistance	NPD	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by :

ALBERTO ALBONETTI
(Technical Director)

Fiorano Modenese
25/06/2013


